

BOSTIK CEMENTONE CONCENTRATED MORTAR PLASTICISER
Supercedes Date: 17-Dec-2020

Revision date 05-Mar-2021
Revision Number 1.09

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BOSTIK CEMENTONE CONCENTRATED MORTAR PLASTICISER
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Building and construction work.
Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited
 Common Rd
 ST16 3EH
 Stafford UK
 Tel: +44 (1785) 27 26 25
 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Emergency Telephone
United Kingdom +44 (1785) 272650
Ireland +353 (1) 8624900 (Monday- Friday 9am-5pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin corrosion/irritation	Category 1 Sub-category B - (H314)
Serious eye damage/eye irritation	Category 1 - (H318)
Skin sensitisation	Category 1 - (H317)

2.2. Label elements

Contains Rosin, fumarated, Sodium hydroxide, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]



Signal word
 Danger

SAFETY DATA SHEET

BOSTIK CEMENTONE CONCENTRATED MORTAR
PLASTICISER
Supercedes Date: 17-Dec-2020

Revision date 05-Mar-2021

Revision Number 1.09

Hazard statements

H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P260 - Do not breathe mist/vapours/spray

P280 - Wear protective gloves and eye/face protection

P302 + P352 - IF ON SKIN: Wash with plenty of water and soap

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P501 - Dispose of contents/ container to an approved waste disposal plant

Additional information

This product requires tactile warnings if supplied to the general public. This product requires child resistant fastenings if supplied to the general public.

2.3. Other hazards

No information available.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Rosin, fumarated	266-040-8	65997-04-8	10 - <20	Eye Dam. 1 (H318) Skin Sens. 1 (H317) Aquatic Chronic 4 (H413)		01-2119494918-16-XXXX
Poly(oxy-1,2-ethanediyl), .alpha.-sulfo-.omega.-hydroxy-, C10-16-alkyl ethers, sodium salts	-	68585-34-2	10 - <20	Skin Irrit. 2 (H315) Eye Irrit. 2 (H319)		[7]
Sodium hydroxide	215-185-5	1310-73-2	1 - <3	Skin Corr. 1A (H314) Met. Corr. 1 (H290)	Eye Irrit. 2 :: 0.5%<=C<2% Skin Corr. 1A :: C>=5% Skin Corr. 1B :: 2%<=C<5% Skin Irrit. 2 :: 0.5%<=C<2%	01-2119457892-27-XXXX

SAFETY DATA SHEET

BOSTIK CEMENTONE CONCENTRATED MORTAR
PLASTICISER
Supercedes Date: 17-Dec-2020

Revision date 05-Mar-2021

Revision Number 1.09

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	611-341-5	55965-84-9	<0.0015	Acute Tox. 3 (H301) Acute Tox. 2 (H310) Acute Tox. 2 (H330) Skin Corr. 1C (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) M Factor Acute = 100 M Factor Chronic = 100	Eye Dam. 1 :: C>=0.6% Irrit. 2 :: 0.06%<=C<0.6% Skin Corr. 1C :: C>=0.6% Skin Irrit. 2 :: 0.06%<=C<0.6% Skin Sens. 1 :: C>=0.0015%	01-2120764691-48-XXXX
--	-----------	------------	---------	--	--	-----------------------

NOTE [7] - No registration number is given for this substance because it is a polymer exempted from registration according to the provisions of Article 2(9) of REACH. All monomers or other substances within the polymer are registered or exempt from registration

Full text of H- and EUH-phrases: see section 16

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur. Get immediate medical advice/attention.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get immediate medical advice/attention. May cause an allergic skin reaction.
Ingestion	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Wear personal protective clothing (see section 8).

SAFETY DATA SHEET

BOSTIK CEMENTONE CONCENTRATED MORTAR
PLASTICISER
Supercedes Date: 17-Dec-2020

Revision date 05-Mar-2021

Revision Number 1.09

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Burning sensation. Itching. Rashes. Hives.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Product is a corrosive material. Use of gastric lavage or emesis is contra-indicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure. May cause sensitisation in susceptible persons. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media No information available.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapours. Product is or contains a sensitisier. May cause sensitisation by skin contact.

Hazardous combustion products Carbon dioxide (CO₂). Nitrogen oxides (NO_x).

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Attention! Corrosive material. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Should not be released into the environment. Do not allow to enter into soil/subsoil. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

SAFETY DATA SHEET

BOSTIK CEMENTONE CONCENTRATED MORTAR
PLASTICISER
Supercedes Date: 17-Dec-2020

Revision date 05-Mar-2021

Revision Number 1.09

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse.

General hygiene considerations Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from moisture. Store locked up. Keep out of the reach of children. Store away from other materials.

7.3. Specific end use(s)

Specific use(s)

Building and construction work.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	Ireland	United Kingdom
Sodium hydroxide 1310-73-2	-	STEL: 2 mg/m ³	STEL: 2 mg/m ³

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration (PNEC) No information available.

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection Tight sealing safety goggles. Face protection shield. Eye protection must conform to standard EN 166.

Hand protection Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for

SAFETY DATA SHEET

BOSTIK CEMENTONE CONCENTRATED MORTAR
PLASTICISER
Supercedes Date: 17-Dec-2020

Revision date 05-Mar-2021

Revision Number 1.09

Skin and body protection information on breakthrough time for specific gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Suitable protective clothing. Gloves made of plastic or rubber. Rubber boots. Wear chemical resistant clothing such as gloves, apron, boots or whole bodysuits made from neoprene, as appropriate.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid	
Appearance	Liquid	
Colour	Brown	
Odour	Slight	
Odour threshold	No information available	
Property	Values	Remarks • Method
pH	11 - 13	
Melting point / freezing point	= 0 °C	
Initial boiling point and boiling range	100 °C	
Flash point	approx	No data available
Evaporation rate		No data available
Flammability		Not applicable for liquids .
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapour pressure	2.6	kPa
Relative vapour density	>1	
Relative density	1.27	
Water solubility	Miscible in water	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature	No data available	
Kinematic viscosity	No data available	
Dynamic viscosity	No data available	
Explosive properties	No data available	
Oxidising properties	No data available	

9.2. Other information

Solid content (%)	No information available
VOC Content (%)	No information available
Liquid Density	1.27

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

SAFETY DATA SHEET

BOSTIK CEMENTONE CONCENTRATED MORTAR
PLASTICISER
Supercedes Date: 17-Dec-2020

Revision date 05-Mar-2021

Revision Number 1.09

Explosion data

Sensitivity to mechanical impact None.
Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Exposure to air or moisture over prolonged periods.

10.5. Incompatible materials

Incompatible materials Acids. Bases. Oxidising agent.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition can lead to release of irritating and toxic gases and vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. Corrosive by inhalation. (based on components). Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye damage. (based on components). Corrosive to the eyes and may cause severe damage including blindness. May cause irreversible damage to eyes.

Skin contact Specific test data for the substance or mixture is not available. Corrosive. (based on components). Causes burns. May cause sensitisation by skin contact. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.

Ingestion Specific test data for the substance or mixture is not available. Causes burns. (based on components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. Burning. May cause blindness. Coughing and/ or wheezing. Itching. Rashes. Hives.

Numerical measures of toxicity

SAFETY DATA SHEET

BOSTIK CEMENTONE CONCENTRATED MORTAR
PLASTICISER
Supercedes Date: 17-Dec-2020

Revision date 05-Mar-2021

Revision Number 1.09

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (dermal) 10,095.00 mg/kg

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Rosin, fumarated 65997-04-8	>2000 mg/kg (Rattus)	= 2000 mg/kg (Rat)	
Sodium hydroxide 1310-73-2	=325 mg/kg (Rattus)	= 1350 mg/kg (Oryctolagus cuniculus)	
reaction mass of 5-chloro-2-methyl-2H-isothiazol-1,3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9	=53 mg/kg (Rattus)	LD50 = 87.12 mg/kg (Oryctolagus cuniculus)	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes burns.

Serious eye damage/eye irritation Classification based on data available for ingredients. Risk of serious damage to eyes. Causes burns.

Respiratory or skin sensitisation May cause sensitisation by skin contact.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SAFETY DATA SHEET

BOSTIK CEMENTONE CONCENTRATED MORTAR
PLASTICISER
Supercedes Date: 17-Dec-2020

Revision date 05-Mar-2021

Revision Number 1.09

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Rosin, fumarated 65997-04-8	EL50 (72hr) >1000 mg/L	LC50 96 h = 38.5 mg/L (Brachydanio rerio (zebra))	-	EC50 (48h) 17 - 100 mg/L (Daphnia Magna)		
Sodium hydroxide 1310-73-2	-	LC50: =45.4mg/L (96h, Oncorhynchus mykiss)	-	-		
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol- 3-one (3:1) [C(M)IT/MIT] 55965-84-9	EC50 (72h) =0.048 mg/L (Pseudokirchner iella subcapitata) (OECD 211)	EC50 (96h) = 0.22 mg/L (Oncorhynchus mykiss) (OECD 211)	-	EC50 (48h) =0.1 mg/L (Daphnia magna) (OECD 202)	100	100

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation No information available.

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9	-	3.16

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment . The product does not contain any substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Rosin, fumarated 65997-04-8	The substance is not PBT / vPvB Further information relevant for the PBT assessment is necessary
Sodium hydroxide 1310-73-2	The substance is not PBT / vPvB PBT assessment does not apply
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9	The substance is not PBT / vPvB

12.6. Other adverse effects

SAFETY DATA SHEET

BOSTIK CEMENTONE CONCENTRATED MORTAR
PLASTICISER
Supercedes Date: 17-Dec-2020

Revision date 05-Mar-2021

Revision Number 1.09

Other adverse effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Do not reuse empty containers.
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Note:

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.

Land transport (ADR/RID)

14.1 UN number or ID number	UN1760
14.2 Proper Shipping Name	Corrosive liquid, n.o.s (Sodium hydroxide, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT])
14.3 Transport hazard class(es)	8
Labels	8
14.4 Packing group	II
Description	UN1760, Corrosive liquid, n.o.s (Sodium hydroxide, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]), 8, II, (E)
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	274
Classification code	C9
Tunnel restriction code	(E)
Limited Quantity (LQ)	1 L
ADR Hazard Id (Kemmller Number)	80

IMDG

14.1 UN number or ID number	UN1760
14.2 Proper Shipping Name	Corrosive liquid, n.o.s (Sodium hydroxide, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT])
14.3 Transport hazard class(es)	8
14.4 Packing group	II
Description	UN1760, Corrosive liquid, n.o.s (Sodium hydroxide, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]), 8, II
14.5 Marine pollutant	NP
14.6 Special Provisions	274
Limited Quantity (LQ)	1 L
EmS-No	F-A, S-B
14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code	Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	UN1760
------------------------------------	--------

SAFETY DATA SHEET

BOSTIK CEMENTONE CONCENTRATED MORTAR
PLASTICISER
Supercedes Date: 17-Dec-2020

Revision date 05-Mar-2021

Revision Number 1.09

14.2 Proper Shipping Name	Corrosive liquid, n.o.s (Sodium hydroxide, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT])
14.3 Transport hazard class(es)	8
14.4 Packing group	II
Description	UN1760, Corrosive liquid, n.o.s (Sodium hydroxide, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]), 8, II
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	A3, A803
Limited Quantity (LQ)	0.5 L
ERG Code	8L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Biocidal Products Regulation (EU) No 528/2012 (BPR)

Contains a biocide : Contains C(M)IT/MIT (3:1). May produce an allergic reaction

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

15.2. Chemical safety assessment

SAFETY DATA SHEET

BOSTIK CEMENTONE CONCENTRATED MORTAR
PLASTICISER
Supercedes Date: 17-Dec-2020

Revision date 05-Mar-2021

Revision Number 1.09

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H290 - May be corrosive to metals
H301 - Toxic if swallowed
H310 - Fatal in contact with skin
H314 - Causes severe skin burns and eye damage
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H319 - Causes serious eye irritation
H330 - Fatal if inhaled
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects
H413 - May cause long lasting harmful effects to aquatic life

Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 05-Mar-2021

Indication of changes

Revision note Not applicable.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet