



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

BOSTIK WOOD H200 ELASTIC
Supersedes Date: 24-Sep-2019

Revision date 24-Sep-2019
Revision Number 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Product Name BOSTIK WOOD H200 ELASTIC
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives.
Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik GmbH
An der Bundesstrasse 16
33829 Borgholzhausen, Germany
Tel: +49 (0) 5425 / 801 0
Fax: +49 (0) 5425 / 801 140

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom +44 (1785) 272650
Ireland +353 (1) 8624900 (Monday- Friday 9am-5pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Not classified

2.2. Label Elements

Not classified

Signal word

None

Hazard statements

Not classified

EU Specific Hazard Statements

EUH210 - Safety data sheet available on request

Precautionary statements

P102 - Keep out of reach of children

2.3. Other Hazards

No information available

PBT and vPvB assessment

United Kingdom, Ireland - BE

SAFETY DATA SHEET

BOSTIK WOOD H200 ELASTIC
Supersedes Date: 24-Sep-2019

Revision date 24-Sep-2019
Revision Number 1

The components in this formulation do not meet the criteria for classification as PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No.	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Silane, ethenyltrimethoxy-	220-449-8	2768-02-7	1- <2.5	Acute Tox. 4 (H332) Flam. Liq. 3 (H226)		01-2119513215-52-XXXX
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	258-207-9	52829-07-9	0.1 - <1	Eye Dam. 1 (H318) Aquatic Acute 1 (H400) Aquatic Chronic 2 (H411)		01-2119537297-32-XXXX

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	If medical advice is needed, have product container or label at hand.
Inhalation	Move victim to fresh air. If symptoms persist, call a doctor.
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes.
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
Ingestion	Call a doctor immediately. Rinse mouth thoroughly with water. Small amounts of toxic methanol are released by hydrolysis.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Treat symptomatically.

SAFETY DATA SHEET

BOSTIK WOOD H200 ELASTIC
Supersedes Date: 24-Sep-2019

Revision date 24-Sep-2019
Revision Number 1

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Thermal decomposition can lead to release of irritating gases and vapours.

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO₂).

5.3. Advice for firefighters

Special protective equipment for fire-fighters Wear self contained breathing apparatus for fire fighting if necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing.

Other information Ventilate the area. Prevent further leakage or spillage if safe to do so.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

Methods for containment Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

General hygiene considerations Avoid contact with skin, eyes or clothing. When using do not eat, drink or smoke. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from moisture. Keep/store only in original container. Keep at temperatures between 5 and 35 °C. Keep away from food, drink and animal feedingstuffs.

SAFETY DATA SHEET

BOSTIK WOOD H200 ELASTIC
Supersedes Date: 24-Sep-2019

Revision date 24-Sep-2019
Revision Number 1

7.3. Specific end use(s)

Specific Use(s)

Adhesives.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Exposure Limits This product, as supplied, does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies

Chemical name	European Union	Ireland	United Kingdom
Limestone 1317-65-3	-	TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³	TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³
Methyl alcohol 67-56-1	TWA: 200 ppm TWA: 260 mg/m ³ *	TWA: 200 ppm TWA: 260 mg/m ³ STEL: 600 ppm STEL: 780 mg/m ³ Sk*	TWA: 200 ppm TWA: 266 mg/m ³ STEL: 250 ppm STEL: 333 mg/m ³ Sk*

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)

Silane, ethenyltrimethoxy- (2768-02-7)

Type	worker Systemic health effects Long term
Exposure route	Inhalation
Derived No Effect Level (DNEL)	27,6 mg/m ³

Type	worker Systemic health effects Long term
Exposure route	Dermal
Derived No Effect Level (DNEL)	3,9 mg/kg bw/d

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Type	worker Short term Long term Systemic health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	2.82 mg/m ³

Type	worker Long term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	1.6 mg/kg

Derived No Effect Level (DNEL)

Silane, ethenyltrimethoxy- (2768-02-7)

Type	Consumer Systemic health effects Long term
Exposure route	Inhalation
Derived No Effect Level (DNEL)	18,9 mg/m ³

Type	Consumer Systemic health effects Long term
Exposure route	Dermal
Derived No Effect Level (DNEL)	7,8 mg/kg bw/d

SAFETY DATA SHEET

BOSTIK WOOD H200 ELASTIC
Supersedes Date: 24-Sep-2019

Revision date 24-Sep-2019
Revision Number 1

Type	Consumer Systemic health effects Long term
Exposure route	Oral
Derived No Effect Level (DNEL)	0,3 mg/kg bw/d

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)	
Type	Consumer Long term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	0.8 mg/kg

Type	Consumer Long term Systemic health effects
Exposure route	Oral
Derived No Effect Level (DNEL)	0.4 mg/kg

Predicted No Effect Concentration (PNEC) No information available.

Predicted No Effect Concentration (PNEC)	
Silane, ethenyltrimethoxy- (2768-02-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.34 mg/l
Marine water	0.034 mg/l
Microorganisms in sewage treatment	110 mg/l

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.018 mg/l
Marine water	0.0018 mg/l
Freshwater sediment	29 mg/kg
Marine sediment	2.9 mg/kg
Soil	5.9 mg/kg

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/face protection	Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166
Hand protection	Wear suitable gloves. Gloves must conform to standard EN 374. Recommended Use: Neoprene™. Nitrile rubber. Butyl rubber. Polyvinyl chloride (PVC). Glove thickness > 0.7mm. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time for the mentioned glove material is in general greater than 480 min.
Skin and body protection	Wear suitable protective clothing.
Respiratory protection	Ensure adequate ventilation, especially in confined areas. In case of insufficient ventilation, wear suitable respiratory equipment. Wear a respirator conforming to EN 140 with Type A/P2 filter or better.
Recommended filter type:	Brown. White.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Paste
Colour	Beige
Odour	Slight Characteristic
Odour threshold	No information available

SAFETY DATA SHEET

BOSTIK WOOD H200 ELASTIC
Supersedes Date: 24-Sep-2019

Revision date 24-Sep-2019
Revision Number 1

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	
Melting point / freezing point	No data available	
Boiling point / boiling range	No data available	
Flash point	> 61 °C	CC (closed cup)
Evaporation rate	No data available	
Flammability (solid, gas)	No data available	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapour pressure	< 1100	hPa @ 50 °C
Vapour density	No data available	
Relative density	1.5	
Water solubility	Reacts with water	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature	No data available	
Kinematic viscosity	No data available	
Dynamic viscosity	No data available	
Explosive properties	No data available	
Oxidising properties	No data available	
9.2. Other information		
Solid content (%)	No information available	
Softening Point	No information available	
Molecular weight	No information available	
VOC Content (%)	< 3 %	Swiss ordinance on the Incentive Tax on Volatile Organic Compounds of 12 Nov 1997
Density	ca. 1.5 g/cm ³	
Bulk density	No information available	

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Product cures with moisture.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion Data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Protect from moisture.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

SAFETY DATA SHEET

BOSTIK WOOD H200 ELASTIC
Supersedes Date: 24-Sep-2019

Revision date 24-Sep-2019
Revision Number 1

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.
Eye contact Based on available data, the classification criteria are not met.
Skin contact Based on available data, the classification criteria are not met.
Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Numerical measures of toxicity

No information available

Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (dermal) 14,092.00 mg/kg
ATEmix (inhalation-vapour) 919.00 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Silane, ethenyltrimethoxy- 2768-02-7	LD50 = 7120 -7236 mg/kg (Rattus) OECD 401	= 3360 µL/kg (Oryctolagus cuniculus)	LC50 (4hr) 16.8 mg/l (Rattus) OECD TG 403
Bis(2,2,6,6-tetramethyl-4-piperi- dyl) sebacate 52829-07-9	LD50 (Rattus) > 2000 mg/kg OECD 423	LD50 (Rattus) > 3 170 mg/kg OECD 402	=500 mg/m ³ (Rattus) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Component Information					
Silane, ethenyltrimethoxy- (2768-02-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal	0.5 mL	24 hours	Non-irritant
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Non-irritant

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

BOSTIK WOOD H200 ELASTIC
Supersedes Date: 24-Sep-2019

Revision date 24-Sep-2019
Revision Number 1

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Component Information			
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig		No sensitisation responses were observed

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Not considered to be harmful to aquatic life.

Chemical name	Algae/aquatic plants	Fish	Toxicity to Micro-organisms	Crustacea	M-Factor
Silane, ethenyltrimethoxy-2768-02-7	EC 50 (72h) > 957 mg/l (Desmodesmus subspicatus) EU Method C.3	LC50 (96h) = 191 mg/l (Oncorhynchus mykiss)	-	EC50(48hr) 168.7mg/l (Daphnia magna)	-
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9	EC50 72Hr 0.705 mg/l (Pseudokirchnerella subcapitata)	LC50 (96h) = 5.29 mg/l (Oryzias latipes)	-	LC50 48Hr 8.58 mg/l (Daphnia magna)	-

12.2. Persistence and degradability

Persistence and degradability No information available.

Component Information			
Silane, ethenyltrimethoxy- (2768-02-7)			
Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	BOD	51 % Not readily biodegradable
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)			
Method	Exposure time	Value	Results
OECD Test No. 303: Simulation Test - Aerobic Sewage Treatment -- A: Activated Sludge Units; B:	28 days	Total organic carbon (TOC)	24 % Moderate

SAFETY DATA SHEET

BOSTIK WOOD H200 ELASTIC
Supersedes Date: 24-Sep-2019

Revision date 24-Sep-2019
Revision Number 1

Biofilms			
----------	--	--	--

12.3. Bioaccumulative potential

Bioaccumulation No information available.

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Silane, ethenyltrimethoxy- 2768-02-7	1.1	-
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9	0.35	-

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment No information available.

Chemical name	PBT and vPvB assessment
Silane, ethenyltrimethoxy- 2768-02-7	The substance is not PBT / vPvB
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9	The substance is not PBT / vPvB

12.6. Other adverse effects

Other adverse effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

European Waste Catalogue 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Other information Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN Number Not regulated
14.2 Proper Shipping Name Not regulated
14.3 Transport hazard class(es) Not regulated
14.4 Packing Group Not regulated
14.5 Environmental hazards Not applicable
14.6 Special Provisions None

IMDG

14.1 UN number Not regulated
14.2 Proper Shipping Name Not regulated

SAFETY DATA SHEET

BOSTIK WOOD H200 ELASTIC
Supersedes Date: 24-Sep-2019

Revision date 24-Sep-2019
Revision Number 1

14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine Pollutant	Np
14.6 Special Provisions	None
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	No information available

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

15.2. Chemical safety assessment

No information available

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H332 - Harmful if inhaled

H226 - Flammable liquid and vapour

H373 - May cause damage to organs through prolonged or repeated exposure

H318 - Causes serious eye damage

H400 - Very toxic to aquatic life

SAFETY DATA SHEET

BOSTIK WOOD H200 ELASTIC
Supersedes Date: 24-Sep-2019

Revision date 24-Sep-2019
Revision Number 1

H411 - Toxic to aquatic life with long lasting effects

Legend

SVHC: Substances of Very High Concern for Authorisation:

Legend SECTION 8: Exposure controls/personal protection

TWA TWA (time-weighted average)

STEL

STEL (Short Term Exposure Limit)

Ceiling Maximum limit value

*

Skin designation

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure

STOT SE Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 24-Sep-2019

Indication of changes

Revision note SDS sections updated, 4, 5, 6, 7, 8, 9, 13, 15.

Training Advice When working with hazardous materials, regular training of operators is required by law

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet