



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

BOSTIK FP404 FIRE RETARDANT PU GUNFOAM
Supersedes Date: 24-Jun-2021

Revision date 19-Nov-2021
Revision Number 2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BOSTIK FP404 FIRE RETARDANT PU GUNFOAM
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Aerosol.
Uses advised against Consumer use

1.3. Details of the supplier of the safety data sheet

Company Name
Bostik Romania SRL
51, Rasaritului Street (DN7)
070000 Buftea
Ilfov
Romania
Phone: +40 372 833 300
Fax: +40 372 833 301
www.bostik.com

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom +44 (1785) 272650
Ireland +353 (1) 8624900 (Monday- Friday 9am-5pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Acute toxicity - Inhalation (Dusts/Mists)	Category 4 - (H332)
Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Respiratory sensitisation	Category 1 - (H334)
Skin sensitisation	Category 1 - (H317)
Carcinogenicity	Category 2 - (H351)
Specific target organ toxicity — single exposure	Category 3 - (H335)
Specific target organ toxicity — repeated exposure	Category 2 - (H373)
Aerosols	Category 1 - (H222, H229)

2.2. Label elements

Contains Isocyanic acid, polymethylenepolyphenylene ester

SAFETY DATA SHEET

BOSTIK FP404 FIRE RETARDANT PU GUNFOAM
Supersedes Date: 24-Jun-2021

Revision date 19-Nov-2021
Revision Number 2



Signal word
Danger

Hazard statements

H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H332 - Harmful if inhaled.
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 - May cause respiratory irritation.
H351 - Suspected of causing cancer.
H373 - May cause damage to organs through prolonged or repeated exposure.
H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.

EU Specific Hazard Statements

EUH204 - Contains isocyanates. May produce an allergic reaction

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P211 - Do not spray on an open flame or other ignition source
P251 - Do not pierce or burn, even after use
P260 - Do not breathe mist/vapours/spray
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves and eye/face protection
P302 + P352 - IF ON SKIN: Wash with plenty of soap and water
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P342 + P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor
P405 - Store locked up
P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable

Special provisions concerning the labelling of certain mixtures

Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. Type A1 according to standard EN 14387) is used. In case of insufficient ventilation and/or through use, the formation of a explosive/highly flammable mixture is possible. During transportation by car the cans should stand upright in the cargo space. As from 24 August 2023 adequate training is required before industrial or professional use.

Additional information

This product requires tactile warnings if supplied to the general public.

2.3. Other hazards

In case of insufficient ventilation and/or through use, the formation of a explosive/highly flammable mixture is possible. During transportation by car the cans should stand upright in the cargo space. The mentioned hazards are valid for the non-reacted content of the can or of the fresh foam. When foaming the propellants are highly flammable. May be harmful if swallowed.

PBT & vPvB

SAFETY DATA SHEET

BOSTIK FP404 FIRE RETARDANT PU GUNFOAM
Supercedes Date: 24-Jun-2021

Revision date 19-Nov-2021
Revision Number 2

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Isocyanic acid, polymethylenepolyphenylene ester	618-498-9	9016-87-9	40 - <80	STOT SE 3 (H335) STOT RE 2 (H373) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Resp. Sens. 1 (H334) Skin Sens. 1 (H317) Carc. 2 (H351) Acute Tox. 4 (H332)	STOT SE 3 :: C>=5% Skin Irrit. 2 :: C>=5% Eye Irrit. 2 :: C>=5% Resp. Sens. 1 :: C>=0.1%	[7]
Phosphorous oxychloride, reaction products with propylene oxide	807-935-0	1244733-77-4	10 - <20	Acute Tox. 4 (H302)		01-2119486772-26-XXXX
Dimethyl ether	204-065-8	115-10-6	5 - <10	Flam. Gas 1 (H220) Press. Gas		01-2119472128-37-XXXX
Halogenated polyetherpolyol	-	68441-62-3	1 - <2.5	Eye Irrit. 2 (H319) Acute Tox. 4 (H302)		[7]

NOTE [7] - No registration number is given for this substance because it is a polymer exempted from registration according to the provisions of Article 2(9) of REACH. All monomers or other substances within the polymer are registered or exempt from registration

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get

SAFETY DATA SHEET

BOSTIK FP404 FIRE RETARDANT PU GUNFOAM
Supersedes Date: 24-Jun-2021

Revision date 19-Nov-2021
Revision Number 2

	medical advice/attention.
Inhalation	Remove to fresh air. May cause allergic respiratory reaction. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Get immediate medical advice/attention.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
Skin contact	May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor. Wash off immediately with soap and plenty of water for at least 15 minutes. Do not use solvents or thinners to dissolve the material.
Ingestion	May produce an allergic reaction. Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. See section 8 for more information. Avoid breathing vapours or mists.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	May cause allergy or asthma symptoms or breathing difficulties if inhaled. Coughing and/or wheezing. Itching. Rashes. Hives. May cause redness and tearing of the eyes. Burning sensation. Difficulty in breathing.
-----------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	May cause sensitisation in susceptible persons. Treat symptomatically.
------------------------	------------------------------------------------------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO ₂). Water spray.
Unsuitable extinguishing media	Full water jet. DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated. Product is or contains a sensitiser. May cause sensitisation by inhalation and skin contact. May cause sensitisation by skin contact.
---------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Hazardous combustion products	Carbon oxides. Carbon monoxide. Carbon dioxide (CO ₂). Nitrogen oxides (NO _x). Hydrogen cyanide. Isocyanates.
--------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.
-----------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------

SAFETY DATA SHEET

BOSTIK FP404 FIRE RETARDANT PU GUNFOAM
Supersedes Date: 24-Jun-2021

Revision date 19-Nov-2021
Revision Number 2

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid breathing vapours or mists.
Other information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.
For emergency responders	Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions	Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.
----------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------

6.3. Methods and material for containment and cleaning up

Methods for containment	Keep out of drains, sewers, ditches and waterways. Stop leak if you can do it without risk. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Flood with water to complete polymerization and scrape off floor.
Methods for cleaning up	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections	See section 8 for more information. See section 13 for more information.
------------------------------------	--------------------------------------------------------------------------

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling	Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapours or mists. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Provide extract ventilation to points where emissions occur. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. Take off contaminated clothing and wash it before reuse.
General hygiene considerations	Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Remove and wash contaminated clothing and gloves, including the inside, before re-use.

7.2. Conditions for safe storage, including any incompatibilities

SAFETY DATA SHEET

BOSTIK FP404 FIRE RETARDANT PU GUNFOAM
Supersedes Date: 24-Jun-2021

Revision date 19-Nov-2021
Revision Number 2

Storage Conditions

Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals. Store locked up. Keep out of the reach of children. Keep/store only in original container. Store in a dry place. Store in a closed container.

7.3. Specific end use(s)

Specific use(s)
Aerosol.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	Ireland	United Kingdom
Isocyanic acid, polymethylenepolyphenylene ester 9016-87-9	-	TWA: 0.005 ppm TWA: 0.02 mg/m ³ STEL: 0.015 ppm STEL: 0.07 mg/m ³ (CAS 101-68-8)	TWA: 0.02 mg/m ³ STEL: 0.07 mg/m ³ SEN; as -NCO
Dimethyl ether 115-10-6	TWA: 1000 ppm TWA: 1920 mg/m ³	TWA: 1000 ppm TWA: 1920 mg/m ³ STEL: 3000 ppm STEL: 5760 mg/m ³	TWA: 400 ppm TWA: 766 mg/m ³ STEL: 500 ppm STEL: 958 mg/m ³
Isobutane 75-28-5	-	TWA: 1000 ppm (8hr) STEL: 1000 ppm	
Propane 74-98-6	-	STEL: 3000 ppm	
Diethylene Glycol 111-46-6	-	TWA: 23 ppm TWA: 100 mg/m ³ STEL: 69 ppm STEL: 300 mg/m ³	TWA: 23 ppm TWA: 101 mg/m ³ STEL: 69 ppm STEL: 303 mg/m ³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
Phosphorous oxychloride, reaction products with propylene oxide (1244733-77-4)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	8.2 mg/m ³	
worker Short term Systemic health effects	Inhalation	22.6 mg/m ³	
worker Long term Systemic health effects	Dermal	2.91 mg/kg bw/d	

Dimethyl ether (115-10-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker	Inhalation	1894 mg/m ³	

SAFETY DATA SHEET

BOSTIK FP404 FIRE RETARDANT PU GUNFOAM
Supersedes Date: 24-Jun-2021

Revision date 19-Nov-2021
Revision Number 2

Long term Systemic health effects			
--------------------------------------	--	--	--

Halogenated polyetherpolyol (68441-62-3)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	6 mg/m ³	
worker Long term Systemic health effects	Dermal	0.87 mg/kg bw/d	

Derived No Effect Level (DNEL)			
Phosphorous oxychloride, reaction products with propylene oxide (1244733-77-4)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	1.45 mg/m ³	
Consumer Short term Systemic health effects	Inhalation	5.6 mg/m ³	
Consumer Long term Systemic health effects	Dermal	1.04 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	0.52 mg/kg bw/d	
Consumer Short term Systemic health effects	Oral	2 mg/kg bw/d	

Dimethyl ether (115-10-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	471 mg/m ³	

Halogenated polyetherpolyol (68441-62-3)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	1.5 mg/m ³	
Consumer Long term Systemic health effects	Dermal	0.435 mg/kg bw/d	

Predicted No Effect Concentration (PNEC) No information available.

Predicted No Effect Concentration (PNEC)	
Phosphorous oxychloride, reaction products with propylene oxide (1244733-77-4)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.32 mg/l
Marine water	0.032 mg/l

SAFETY DATA SHEET

BOSTIK FP404 FIRE RETARDANT PU GUNFOAM
Supersedes Date: 24-Jun-2021

Revision date 19-Nov-2021
Revision Number 2

Sewage treatment plant	19.1 mg/l
Freshwater sediment	11.5 mg/kg dry weight
Marine sediment	1.15 mg/kg dry weight
Soil	0.34 mg/kg dry weight

Dimethyl ether (115-10-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.155 mg/l
Marine water	0.016 mg/l
Microorganisms in sewage treatment	160 mg/l
Freshwater sediment	0.681 mg/kg dry weight
Soil	0.45 mg/kg dry weight

8.2. Exposure controls

Engineering controls	Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.
Personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166
Hand protection	Wear suitable gloves. Glove thickness > 0.7mm. Butyl rubber. Nitrile rubber. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374
Skin and body protection	Wear appropriate personal protective clothing to prevent skin contact.
Respiratory protection	Ensure adequate respiratory protection during spray applications. In case of insufficient ventilation, wear suitable respiratory equipment.
Recommended filter type:	Organic gases and vapours filter conforming to EN 14387. Wear a respirator conforming to EN 140 with Type A filter or better.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Foam
Colour	No information available
Odour	Characteristic
Odour threshold	No information available

Property	Values	Remarks • Method
pH	No data available	Not applicable Insoluble in water
pH (as aqueous solution)	No data available	
Melting point / freezing point	No data available	
Initial boiling point and boiling range	Not applicable, Aerosol .	Not applicable, Aerosol
Flash point	Not applicable, Aerosol .	Not applicable, Aerosol
Evaporation rate	No data available	
Flammability	No data available	
Flammability Limit in Air		
Upper flammability or explosive limits	18.6	
Lower flammability or explosive limits	1.7	
Vapour pressure	600	kPa @ 20 °C
Relative vapour density	No data available	
Relative density	No data available	
Water solubility	Immiscible in water	

SAFETY DATA SHEET

BOSTIK FP404 FIRE RETARDANT PU GUNFOAM
Supersedes Date: 24-Jun-2021

Revision date 19-Nov-2021
Revision Number 2

Solubility(ies)	No data available
Partition coefficient	No data available
Autoignition temperature	No data available
Decomposition temperature	No data available
Kinematic viscosity	No data available
Dynamic viscosity	No data available
Explosive properties	No data available
Oxidising properties	No data available

9.2. Other information

Solid content (%)	No information available	
VOC Content (%)	160.5 g/L	European directive n°2010/75/UE
Liquid Density	1.049 g/cm ³	

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact	None.
Sensitivity to static discharge	Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Heat, flames and sparks. Excessive heat. Protect from moisture. Keep away from open flames, hot surfaces and sources of ignition. Extremes of temperature and direct sunlight.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents. Water. Alcohols. Amines. Incompatible with oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Specific test data for the substance or mixture is not available. May cause
------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------

SAFETY DATA SHEET

BOSTIK FP404 FIRE RETARDANT PU GUNFOAM
Supersedes Date: 24-Jun-2021

Revision date 19-Nov-2021
Revision Number 2

sensitisation in susceptible persons. (based on components). May cause irritation of respiratory tract. Harmful by inhalation.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.

Skin contact Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). May cause sensitisation by skin contact. Causes skin irritation.

Ingestion Specific test data for the substance or mixture is not available. May cause additional effects as listed under "Inhalation". Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea. May be harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or flushing. Coughing and/ or wheezing. Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes.

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 3,291.70 mg/kg
ATEmix (inhalation-dust/mist) 3.27 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Isocyanic acid, polymethylenepolyphenylene ester 9016-87-9	LD50 > 10000 mg/kg (Rattus)	LD 50 > 9400 mg/kg (Oryctolagus cuniculus)	=1.5 mg/L (Rattus) 4 h
Phosphorous oxychloride, reaction products with propylene oxide 1244733-77-4	LD50 > 500 mg/kg (males); LD50 = 632 mg/kg (females)(Rattus)	LD50 >2000 mg/Kg (Rattus) (OECD 402)	LD50 >7 mg/L (4h)(Rattus) (OECD 403)
Dimethyl ether 115-10-6			=164000 ppm (Rattus) 4 h
Halogenated polyetherpolyol 68441-62-3	LD50 = 1337 mg/Kg (Rattus) (OECD 401)		

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Irritating to skin.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitisation May cause sensitisation by inhalation. May cause sensitisation by skin contact.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

BOSTIK FP404 FIRE RETARDANT PU GUNFOAM
Supersedes Date: 24-Jun-2021

Revision date 19-Nov-2021
Revision Number 2

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for ingredients. Suspected of causing cancer.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause respiratory irritation.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Isocyanic acid, polymethylenepolyphenylene ester 9016-87-9	ErC50 (72h) >1640 mg/L Algae (scenedesmus subspicatus) (OECD 201)	CL50 (96h) >1000 mg/L (Danio rerio)	-	EC50 (24H) >1000 mg/L Daphnia magna		
Phosphorous oxychloride, reaction products with propylene oxide 1244733-77-4	ErC50 (72h) = 82 mg/L (Pseudokirchneriella subcapitata) OECD 201	LC50 (96h) = 56.2 mg/L (Brachydanio rerio) Static	-	LC50 (48h) = 131 mg/L Daphnia magna		
Dimethyl ether 115-10-6	-	LC50: >4.1g/L (96h, Poecilia reticulata)	-	> 4400 mg/L (Daphnia) (NEN 6501)		
Halogenated polyetherpolyol 68441-62-3	-	LC50: =560mg/L (96h, Poecilia reticulata)	-	-		

12.2. Persistence and degradability

Persistence and degradability No information available.

SAFETY DATA SHEET

BOSTIK FP404 FIRE RETARDANT PU GUNFOAM
Supersedes Date: 24-Jun-2021

Revision date 19-Nov-2021
Revision Number 2

Component Information			
Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9)			
Method	Exposure time	Value	Results
OECD Test No. 302C: Inherent Biodegradability: Modified MITI Test (II)	28 days	0% biodegradation	Not readily biodegradable

Halogenated polyetherpolyol (68441-62-3)			
Method	Exposure time	Value	Results
OECD Test No. 301D: Ready Biodegradability: Closed Bottle Test (TG 301 D)	28 days	16%	Not readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Isocyanic acid, polymethylenepolyphenylene ester 9016-87-9	-	< 14
Phosphorous oxychloride, reaction products with propylene oxide 1244733-77-4	2.68	-
Dimethyl ether 115-10-6	-0.18	-
Halogenated polyetherpolyol 68441-62-3	3.3	-

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT).

Chemical name	PBT and vPvB assessment
Phosphorous oxychloride, reaction products with propylene oxide 1244733-77-4	The substance is not PBT / vPvB
Dimethyl ether 115-10-6	The substance is not PBT / vPvB
Halogenated polyetherpolyol 68441-62-3	The substance is not PBT / vPvB

12.6. Other adverse effects

Other adverse effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

SAFETY DATA SHEET

BOSTIK FP404 FIRE RETARDANT PU GUNFOAM
Supersedes Date: 24-Jun-2021

Revision date 19-Nov-2021
Revision Number 2

Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.
Waste codes / waste designations according to EWC / AVV	16 05 05 gases in pressure containers other than those mentioned in 16 05 04. Waste codes should be assigned by the user based on the application for which the product was used.
European Waste Catalogue	08 05 01* waste isocyanates 16 05 04* gases in pressure containers (including halons) containing dangerous substances 17 06 04 insulation materials other than those mentioned in 17 06 01 and 17 06 03
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Note: The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.

Land transport (ADR/RID)

14.1 UN number or ID number	UN1950
14.2 Proper Shipping Name	Aerosols
14.3 Transport hazard class(es)	2
Labels	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, 2, (D)
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	190, 327, 344, 625
Classification code	5F
Tunnel restriction code	(D)
Limited quantity (LQ)	1 L

IMDG

14.1 UN number or ID number	UN1950
14.2 Proper Shipping Name	Aerosols
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, 2.1, (0°C c.c.)
14.5 Marine pollutant	NP
14.6 Special Provisions	63, 190, 277, 327, 344, 381, 959
Limited Quantity (LQ)	See SP277
EmS-No	F-D, S-U
14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code	Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	UN1950
14.2 Proper Shipping Name	Aerosols, flammable
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, flammable, 2.1
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	A145, A167, A802
Limited quantity (LQ)	30 kg G
ERG Code	10L

SAFETY DATA SHEET

BOSTIK FP404 FIRE RETARDANT PU GUNFOAM
Supersedes Date: 24-Jun-2021

Revision date 19-Nov-2021
Revision Number 2

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
Isocyanic acid, polymethylenepolyphenylene ester	9016-87-9	56 74.
Diisocyanates	--	74

56 . If product supplied to the general public with substance $\geq 0.1\%$, then gloves must be provided with the product. **74** If product supplied to the industrial or professional users with total monomeric diisocyanates $\geq 0.1\%$, then its packaging must mention "As from 24 August 2023 adequate training is required before industrial or professional use".

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P3a - FLAMMABLE AEROSOLS

P3b - FLAMMABLE AEROSOLS

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

SAFETY DATA SHEET

BOSTIK FP404 FIRE RETARDANT PU GUNFOAM
Supersedes Date: 24-Jun-2021

Revision date 19-Nov-2021
Revision Number 2

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H220 - Extremely flammable gas
H302 - Harmful if swallowed
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335 - May cause respiratory irritation
H351 - Suspected of causing cancer
H373 - May cause damage to organs through prolonged or repeated exposure

Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 19-Nov-2021

Indication of changes

Revision note SDS sections updated, 2, 3, 4, 5, 6, 7, 8, 10, 11, 12, 13, 15.

Training Advice AS FROM 24 AUGUST 2023 ADEQUATE TRAINING IS REQUIRED BEFORE INDUSTRIAL OR PROFESSIONAL USE

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet