

# Advanced Gloss

Oil-like finish with water-based convenience and durability.



## PRODUCT DESCRIPTION

Advanced Gloss is a high-performance water-based trim paint designed for interior and exterior wood, metal, and furniture. Delivering the flow and levelling of traditional solvent-based gloss without the odour or yellowing, it provides a tough, high-sheen finish that's quick-drying, low VOC, and easy to apply.

## USES

- Interior and exterior doors and windows
- Skirting boards and architraves
- Wooden furniture and cabinetry
- Metal gates and railings
- Radiators and pipework

## CHARACTERISTICS / ADVANTAGES

- Excellent durability
- LRV Rating 90 (White)
- Applies & finishes like a traditional solvent borne gloss paint
- Non yellowing
- Very low VOC
- Low odour
- Quick drying

## APPROVALS / STANDARDS

### VOC Content

- 2004/42/EC EU limit value for this product (cat.A/b WB): 100g/l (2010) This product contains max. 35g/l VOC.

### EPD

- Independent verification of the declaration and data according to EN ISO 14025:2010

### Quality Control


- Manufactured under the auspices of ISO 9001:2015 quality & ISO 14001:2015 environmental management systems.



## Need help? Speak to the experts

Our dedicated team are here to help. If you have any queries on this product, or any product in the Fleetwood range, queries about preparation or application, or can't find your required colour, call us today

Technical Assistance: Email: [technical@fleetwood.ie](mailto:technical@fleetwood.ie) Tel: +353 49 854 7209 (weekdays 9am-5pm)  
 Colour Advice: Tel: +353 49 854 7209 (weekdays 9am-5pm Saturdays 8am - 4.30pm)



## Colour

**Colours** Brilliant White & Tinted to Various Colours

**Colour Collections** Fleetwood Colour Perfect, NCS, Sherwin Williams, Pantone, BS British Standard, & RAL



SHERWIN  
WILLIAMS

PANTONE®



## Specification

<b>Composition</b>	Hybrid of acrylic and alkyd emulsions.
<b>Number of Components</b>	1
<b>Recommended number of coats</b>	2 coats are recommended. Coverage may vary depending on the profile, porosity of the substrate and application method.
<b>Usage Interior/Exterior</b>	Interior.
<b>Application Tools</b>	Brush, roller or spray.
<b>Coverage</b>	Approx. 16m <sup>2</sup> per litre, per coat can be achieved on non-porous surfaces under normal conditions..
<b>Overcoat Times</b>	Recoat after 2 - 4 hours.
<b>Curing Time</b>	Touch dry in 30 minutes, fully cured after 7 to 10 days.
<b>Suitable For</b>	New or previously painted drywall, plaster, cement, concrete and other paintable surfaces.
<b>Min. application temperature</b>	5°C
<b>Pack Size</b>	1 L, 2.5 L
<b>Shelf Life</b>	3 years in unopened container.
<b>Storage</b>	Do not allow to freeze.
<b>Cleaning Tools</b>	Wash application tools in warm, soapy water immediately after use. .
<b>Principle Limitations</b> Please contact us regarding applications not described here	Not intended for application to floors or any surface subject to water immersion or prolonged contact with water including shower enclosures, saunas, steam rooms. Not recommended for use in HVAC duct work.

## Product Information

<b>Pack Sizes:</b>	1 L, 2.5 L
<b>Colour Range:</b>	Brilliant White & Tinted to Various Colours
<b>LRV Range:</b>	90 (White).
<b>VOC Content:</b>	Contains max VOC: 35g/l Conforms to EU 2010 Directive (Cat A/b) 100g/l
<b>Composition:</b>	Pigment: Lightfast Pigments Binder: Hybrid of acrylic and alkyd emulsion Solvent: Water
<b>Solids:</b>	Volume Solids: 39.0% (+/- 2%) Weight Solids: 47.0% (+/- 2%) Specific Gravity: 1.14 (+/- 0.15) Gloss: > 85 at 60° pH: > 8.50
<b>Technical Data Sheet</b> Advanced Gloss - F 333	

## Product Information Cont.

<b>Surface Preparation:</b>	Surfaces to be painted must be in sound condition. Use in accordance with good painting practice. Remove oil, grease and flaking material Prime bare wood surfaces with Fleetwood Advanced Primer Undercoat. Prime all other bare surfaces with an appropriate primer. Rub down previously painted surfaces with fine abrasive paper and rinse thoroughly. Avoid dust inhalation.
<b>Application:</b>	Brush, roller, spray & airless spray. Ensure temperature (air, surface, material) 10°C to 42°C (at least 4°C above dew point) Relative humidity max. 75%
<b>Spreading Rate:</b>	As a guide, a coverage rate of up to 16m <sup>2</sup> per litre, per coat can be achieved under normal conditions
<b>Reduction:</b>	Reduce by up to 20% as required by application and/or equipment.
<b>Spray Recommendations:</b>	Conventional Spray: Satisfactory through most equipment Airless Spray: A typical recommendation for airless spray application is a minimum working pressure on paint of 140 kg/cm <sup>2</sup> (2000 lb/in <sup>2</sup> ) with a spray tip size of 0.38mm to 0.46mm (15 - 18thou) spray tip angle 65°. Filter mesh 60.
<b>Drying Time:</b>	Touch Dry: 30 minutes Recoat: 2 – 4 hours This is dependent upon temperature and humidity. Darker colours may take longer. 26°C and 50% relative humidity @ 4 Thou wet.
<b>Cleaning Up:</b>	Clean up with soap and water. After cleaning, be sure to flush spray equipment with solvent to prevent rusting following manufacturer's instructions. Dispose of can in accordance with local authority guidelines.
<b>Tinting Instructions:</b>	Tint only with Fleetwood Tinting systems
<b>Previously Painted Surfaces:</b>	All surfaces to be painted should be clean, dry and free from loose and flaking material. Glossy surfaces must be rubbed down to provide a key. Stir well before use. Avoid overspreading. For best results use a good quality synthetic brush. If using a roller lay off to avoid pin-holing.
<b>Precautions:</b>	Keep out of reach of children. Ensure good ventilation during application and drying. If the product comes in contact with the eyes, rinse immediately with plenty of water. To remove splashes from skin, use soap and water or a recognised skin cleanser. Do not take internally. Contains no added lead.

### Limitations:

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We do not hold guarantee for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice. If you have any queries or concerns about using this product, please contact us before application at +353 49 854 7209 or technical@fleetwood.ie