SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878



SUPER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

: SUPER Product name **Registration number REACH** Product type REACH

: Not applicable (mixture)

: Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Adhesive Sealing compound

1.2.2 Uses advised against

No uses advised against known

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

TEC7* Industrielaan 5B B-2250 Olen +32 14 85 97 37 ₲ +32 14 85 97 38 info@tec7.be *TEC7 is a registered trademark of Novatech International N.V.

Manufacturer of the product

Novatech International N.V. Industrielaan 5B B-2250 Olen +32 14 85 97 37 **i ⊟** +32 14 85 97 38 info@novatech.be

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch) : +32 14 58 45 45 (BIG)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classified as danger	lassified as dangerous according to the criteria of Regulation (EC) No 1272/2008							
Class Category Hazard statements								
Skin Irrit.	category 2	H315: Causes skin irritation.						
Eye Irrit.	category 2	H319: Causes serious eye irritation.						
STOT SE	category 3	H335: May cause respiratory irritation.						

2.2. Label elements

Contains: ethyl 2-cyand	pacrylate.		
Signal word	Warning		
H-statements			
H315	Causes skin irritation.		
H319	Causes serious eye irritation.		
H335	May cause respiratory irritation.		
P-statements			
P101	If medical advice is needed, have product cont	ainer or label at hand.	
P102	Keep out of reach of children.		
P280	Wear protective gloves, protective clothing and	eye protection/face protection.	
P271	Use only outdoors or in a well-ventilated area.		
P264	Wash hands thoroughly after handling.		
Created by: Brandweerinformatie	centrum voor gevaarlijke stoffen vzw (BIG)	Publication date: 2000-09-22	-en
Technische Schoolstraat 43 A, B-2	440 Geel	Date of revision: 2022-07-28	034
http://www.big.be			33-
© BIG vzw			164
Reason for revision: 3; 9; 12			878-16433-034-en
Revision number: 1100		BIG number: 32181	1/13

P304 + P340 P305 + P351 + P338 IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulation.

P501 Supplemental information EUH202

P405

Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

2.3. Other hazards

No other hazards known

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark	M-factors and ATE
ethyl 2-cyanoacrylate 01-2119527766-29	7085-85-0 230-391-5	70% <c<90%< td=""><td>Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 STOT SE 3; H335: C≥10%, (CLP Annex VI (ATP 0))</td><td>(1)(2)(10)</td><td>Constituent</td><td></td></c<90%<>	Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 STOT SE 3; H335: C≥10%, (CLP Annex VI (ATP 0))	(1)(2)(10)	Constituent	
1,4-dihydroxybenzene 01-2119524016-51	123-31-9 204-617-8	C<0.1%	Muta. 2; H341 Carc. 2; H351 Skin Sens. 1; H317 Acute Tox. 4; H302 Eye Dam. 1; H318 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	(1)(2)(10)	Constituent	M: 10

(1) For H- and EUH-statements in full: see section 16

(2) Substance with a Community workplace exposure limit

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

Observe (own) safety. If possible, approach victim and check vital functions. In case of injury and/or intoxication, call the European emergency number 112. Treat symptoms starting with most life-threatening injuries and disorders. Keep victim under observation, possibility of delayed symptoms.

After inhalation:

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

After skin contact:

Do not pull surfaces apart with a direct opposing action. Immerse the bonded surfaces in warm, soapy water. Peel or roll surfaces apart with a blunt edge, e.g. spatula. Consult a doctor/medical service.

After eye contact:

Do not try to open the eyes by manipulation. Wash thoroughly with warm water. Apply a moist gauze patch. Consult a doctor/medical service. After ingestion:

Do not try to pull the lips with a direct opposing action. Apply lots of warm water and saliva. Immediately consult a doctor/medical service.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms After inhalation:

Irritation of the respiratory tract. Irritation of the nasal mucous membranes. Respiratory difficulties.

After skin contact: Tingling/irritation of the skin.

After eye contact:

Irritation of the eye tissue.

After ingestion: No effects known.

4.2.2 Delayed symptoms

No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

Reason for revision: 3; 9; 12

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Small fire: Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting class B foam extinguisher, Quick-acting CO2 extinguisher.

Major fire: Class B foam (alcohol-resistant), Water spray if puddle cannot expand.

5.1.2 Unsuitable extinguishing media:

Small fire: Water (quick-acting extinguisher, reel); risk of puddle expansion. Major fire: Water; risk of puddle expansion.

5.2. Special hazards arising from the substance or mixture

On burning: release of toxic and corrosive gases/vapours (nitrous vapours, carbon monoxide - carbon dioxide). At very high temperature: release of toxic/combustible gases/vapours (hydrogen cyanide). Polymerizes on exposure to water (moisture) and on exposure to temperature rise: pressure rise and possible bursting of container.

5.3. Advice for firefighters

5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Do not move the load if exposed to heat. Dilute toxic gases with water spray. Take account of toxic/corrosive precipitation water.

5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Face shield (EN 166). Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No naked flames.

6.1.1 Protective equipment for non-emergency personnel

See section 8.2

6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Face shield (EN 166). Protective clothing (EN 14605 or EN 13034). Suitable protective clothing

See section 8.2

6.2. Environmental precautions

Contain released product.

6.3. Methods and material for containment and cleaning up

Take up liquid spill into inert absorbent material. Scoop absorbed substance into closing containers. Clean contaminated surfaces with an excess of water. Wash clothing and equipment after handling.

6.4. Reference to other sections

See section 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Keep away from naked flames/heat. Gas/vapour heavier than air at 20°C. Observe normal hygiene standards. Remove contaminated clothing immediately. Avoid contact of substance with water. Keep container tightly closed.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Storage temperature: 2 °C - 8 °C. Meet the legal requirements. Store in a cool area. Store in a dry area. Keep out of direct sunlight. Keep container in a well-ventilated place. Keep only in the original container.

7.2.2 Keep away from:

Heat sources, (strong) acids, oxidizing agents, water/moisture.

7.2.3 Suitable packaging material:

Polyethylene.

7.2.4 Non suitable packaging material:

No data available

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

Reason for revision: 3; 9; 12

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

ailahle th , ill be listed belo

2-Cyanoacrylate d'éthyle		Time-weight	ted average expos	ure limit 8 h		0.2 ppm
		Time-weight	ted average expos	ure limit 8 h		1.04 mg/m
Hydroquinone		Time-weighted average exposure limit 8 h				1 mg/m³
France						
Hydroquinone		-	ted average expos re indicative)	ure limit 8 h (VL: Vale	eur non	2 mg/m ³
Austria						
1,4-Dihydroxybenzol		Tagesmittelv	wert (MAK)			2 mg/m ³
		-	t 5(Mow) 8x (MAK)		4 mg/m ³
Cyanacrylsäureethylester		Tagesmittel	· /			2 ppm
		Tagesmittel	wert (MAK)			9 mg/m ³
UK						_
Ethyl cyanoacrylate				exposure limit (EH40/		0.3 ppm
				exposure limit (EH40/		1.5 mg/m
Hydroquinone		Time-weight (EH40/2005)		ure limit 8 h (Workpl	ace exposure limit	0.5 mg/m ³
USA (TLV-ACGIH)						_
Cyanoacrylates, Ethyl and Meth	ıyl			ure limit 8 h (TLV - A	dopted Value)	0.2 ppm
			alue (TLV - Adopte	,		1 ppm
Hydroquinone b) National biological limit values		Time-weight	ted average expos	ure limit 8 h (TLV - A	dopted Value)	1 mg/m ³
If limit values are applicable and av USA (BEI-ACGIH) Methemoglobin inducers	vailable these will be listed b			5 % of hemoglobin	Background, Nonsp	ecific
(Methemoglobin)	-					
2 Sampling methods						
Product name		Test		Number		
Product name Ethyl 2-Cyanoacrylate		OSHA		55		
Product name Ethyl 2-Cyanoacrylate Hydroquinone Hydroquinone 3 Applicable limit values when usi		OSHA NIOSH OSHA re as intended				
Product name Ethyl 2-Cyanoacrylate Hydroquinone Hydroquinone		OSHA NIOSH OSHA re as intended		55 5004		
Product name Ethyl 2-Cyanoacrylate Hydroquinone 3 Applicable limit values when usi If limit values are applicable an 4 Threshold values DNEL/DMEL - Workers		OSHA NIOSH OSHA re as intended		55 5004	Remark	
Product name Ethyl 2-Cyanoacrylate Hydroquinone 3 Applicable limit values when usi If limit values are applicable an 4 Threshold values DNEL/DMEL - Workers ethyl 2-cyanoacrylate	d available these will be Type Long-term systemic e	OSHA NIOSH OSHA re as intended e listed below ffects inhalat	v.	55 5004 2094 Value 9.25 mg/m ³	Remark	
Product name Ethyl 2-Cyanoacrylate Hydroquinone 3 Applicable limit values when usi If limit values are applicable an 4 Threshold values DNEL/DMEL - Workers ethyl 2-cyanoacrylate Effect level (DNEL/DMEL)	d available these will be Type Long-term systemic e Acute systemic effect	OSHA NIOSH OSHA e listed below ffects inhalat	v.	55 5004 2094 Value 9.25 mg/m ³ 9.25 mg/m ³	Remark	
Product name Ethyl 2-Cyanoacrylate Hydroquinone 3 Applicable limit values when usi If limit values are applicable an 4 Threshold values DNEL/DMEL - Workers ethyl 2-cyanoacrylate Effect level (DNEL/DMEL)	Type Long-term systemic e Acute systemic effect Long-term local effect	OSHA NIOSH OSHA re as intended e listed below ffects inhalat is inhalation ts inhalation	v.	55 5004 2094 Value 9.25 mg/m ³ 9.25 mg/m ³	Remark	
Product name Ethyl 2-Cyanoacrylate Hydroquinone Applicable limit values when usi If limit values are applicable an A Threshold values DNEL/DMEL - Workers ethyl 2-cyanoacrylate Effect level (DNEL/DMEL) DNEL	d available these will be Type Long-term systemic e Acute systemic effect	OSHA NIOSH OSHA re as intended e listed below ffects inhalat is inhalation ts inhalation	v.	55 5004 2094 Value 9.25 mg/m ³ 9.25 mg/m ³	Remark	
Product name Ethyl 2-Cyanoacrylate Hydroquinone Applicable limit values when usi If limit values are applicable an Threshold values DNEL/DMEL - Workers ethyl 2-cyanoacrylate Effect level (DNEL/DMEL) DNEL 1,4-dihydroxybenzene	Type Long-term systemic e Acute systemic effect Long-term local effects inl	OSHA NIOSH OSHA re as intended e listed below ffects inhalat is inhalation ts inhalation	v.	55 5004 2094 9.25 mg/m ³ 9.25 mg/m ³ 9.25 mg/m ³	Remark	
Product name Ethyl 2-Cyanoacrylate Hydroquinone Applicable limit values when usi If limit values are applicable an A Threshold values DNEL/DMEL - Workers ethyl 2-cyanoacrylate Effect level (DNEL/DMEL) DNEL	Type Long-term systemic e Acute systemic effect Long-term local effect	OSHA NIOSH OSHA e listed below ffects inhalat is inhalation ts inhalation halation	ion	55 5004 2094 Value 9.25 mg/m ³ 9.25 mg/m ³		
Product name Ethyl 2-Cyanoacrylate Hydroquinone Hydroquinone 3 Applicable limit values when usi If limit values are applicable an 4 Threshold values DNEL/DMEL - Workers ethyl 2-cyanoacrylate Effect level (DNEL/DMEL) DNEL 1.4-dihydroxybenzene Effect level (DNEL/DMEL)	Type Long-term systemic e Acute systemic effect Long-term local effects inf Acute local effects inf	OSHA NIOSH OSHA re as intended e listed below ffects inhalation ts inhalation halation	ion	55 5004 2094 9.25 mg/m ³ 9.25 mg/m ³ 9.25 mg/m ³ 9.25 mg/m ³	Remark	
Product name Ethyl 2-Cyanoacrylate Hydroquinone Applicable limit values when usi If limit values are applicable an A Threshold values DNEL/DMEL - Workers ethyl 2-cyanoacrylate Effect level (DNEL/DMEL) DNEL I.4-dihydroxybenzene Effect level (DNEL/DMEL) DNEL DNEL DNEL DNEL DNEL DNEL	Type Long-term systemic e Acute systemic effect Long-term local effect Acute local effects inl Type Long-term systemic e Long-term systemic e	OSHA NIOSH OSHA re as intended e listed below ffects inhalation ts inhalation halation	ion	55 5004 2094 9.25 mg/m ³ 9.25 mg/m ³ 9.25 mg/m ³ 9.25 mg/m ³ Value 2.1 mg/m ³ 3.33 mg/kg bw/da	Remark	
Product name Ethyl 2-Cyanoacrylate Hydroquinone Hydroquinone 3 Applicable limit values when usi If limit values are applicable an 4 Threshold values DNEL/DMEL - Workers ethyl 2-cyanoacrylate Effect level (DNEL/DMEL) DNEL I.4-dihydroxybenzene Effect level (DNEL/DMEL) DNEL Effect level (DNEL/DMEL) DNEL Effect level (DNEL/DMEL)	Type Long-term systemic e Acute systemic effect Long-term local effects Acute local effects inl Type Long-term systemic e Long-term systemic e	OSHA NIOSH OSHA re as intended e listed below ffects inhalation ts inhalation halation ffects inhalat ffects dermal	ion ion	55 5004 2094 9.25 mg/m ³ 9.25 mg/m ³ 9.25 mg/m ³ 9.25 mg/m ³ Value 2.1 mg/m ³ 3.33 mg/kg bw/da	Remark	
Product name Ethyl 2-Cyanoacrylate Hydroquinone Applicable limit values when usi If limit values are applicable an A Threshold values DNEL/DMEL - Workers ethyl 2-cyanoacrylate Effect level (DNEL/DMEL) DNEL I.4-dihydroxybenzene Effect level (DNEL/DMEL) DNEL DNEL DNEL DNEL DNEL DNEL	Type Long-term systemic e Acute systemic effect Long-term local effects Acute local effects inl Type Long-term systemic e	OSHA NIOSH OSHA re as intended e listed below ffects inhalation ts inhalation halation ffects inhalat ffects dermal	ion ion	55 5004 2094 Value 9.25 mg/m ³ 9.25 mg/m ³ 9.25 mg/m ³ Value 2.1 mg/m ³ 3.33 mg/kg bw/da Value 9.25 mg/m ³	Remark	
Product name Ethyl 2-Cyanoacrylate Hydroquinone Hydroquinone 3 Applicable limit values when usi If limit values are applicable an 4 Threshold values DNEL/DMEL - Workers ethyl 2-cyanoacrylate Effect level (DNEL/DMEL) DNEL I.4-dihydroxybenzene Effect level (DNEL/DMEL) DNEL Effect level (DNEL/DMEL) DNEL Effect level (DNEL/DMEL)	Type Long-term systemic e Acute systemic effect Long-term local effects inl Type Long-term systemic e Acute systemic e Acute systemic e Long-term systemic e Acute systemic effect	OSHA NIOSH OSHA re as intended e listed below ffects inhalation ts inhalation halation ffects inhalat ffects dermal	ion ion	55 5004 2094 Value 9.25 mg/m ³ 9.25 mg/m ³ 9.25 mg/m ³ Value 2.1 mg/m ³ 3.33 mg/kg bw/da Value 9.25 mg/m ³	Remark	
Product name Ethyl 2-Cyanoacrylate Hydroquinone Hydroquinone 3 Applicable limit values when usi If limit values are applicable an 4 Threshold values DNEL/DMEL - Workers ethyl 2-cyanoacrylate Effect level (DNEL/DMEL) DNEL I.4-dihydroxybenzene Effect level (DNEL/DMEL) DNEL Effect level (DNEL/DMEL) DNEL Effect level (DNEL/DMEL)	Type Long-term systemic e Acute systemic effect Long-term local effects inl Type Long-term systemic e Acute systemic effect Long-term local effect	OSHA NIOSH OSHA re as intended e listed below ffects inhalation ts inhalation halation ffects inhalat ffects dermal ffects inhalat s inhalation ts inhalation	ion ion	55 5004 2094 9.25 mg/m ³ 9.25 mg/m ³ 9.25 mg/m ³ 9.25 mg/m ³ Value 2.1 mg/m ³ 3.33 mg/kg bw/da Value 9.25 mg/m ³ 9.25 mg/m ³	Remark	
Product name Ethyl 2-Cyanoacrylate Hydroquinone Hydroquinone 3 Applicable limit values when usi If limit values are applicable an 4 Threshold values DNEL/DMEL - Workers ethyl 2-cyanoacrylate Effect level (DNEL/DMEL) DNEL I.4-dihydroxybenzene Effect level (DNEL/DMEL) DNEL DNEL DNEL Effect level (DNEL/DMEL) DNEL	Type Long-term systemic e Acute systemic effect Long-term local effects inl Type Long-term systemic e Acute systemic e Acute systemic e Long-term systemic e Acute systemic effect	OSHA NIOSH OSHA re as intended e listed below ffects inhalation ts inhalation halation ffects inhalat ffects dermal ffects inhalat s inhalation ts inhalation	ion ion	55 5004 2094 Value 9.25 mg/m ³ 9.25 mg/m ³ 9.25 mg/m ³ Value 2.1 mg/m ³ 3.33 mg/kg bw/da Value 9.25 mg/m ³	Remark	
Product name Ethyl 2-Cyanoacrylate Hydroquinone Hydroquinone 3 Applicable limit values when usi If limit values are applicable an 4 Threshold values DNEL/DMEL - Workers ethyl 2-cyanoacrylate Effect level (DNEL/DMEL) DNEL I.4-dihydroxybenzene Effect level (DNEL/DMEL) DNEL DNEL DNEL Effect level (DNEL/DMEL) DNEL	Type Long-term systemic e Acute systemic effect Long-term local effects inl Type Long-term systemic e Acute systemic effect Long-term local effect	OSHA NIOSH OSHA re as intended e listed below ffects inhalation ts inhalation halation ffects inhalat ffects dermal ffects inhalat s inhalation ts inhalation	ion ion	55 5004 2094 9.25 mg/m ³ 9.25 mg/m ³ 9.25 mg/m ³ 9.25 mg/m ³ Value 2.1 mg/m ³ 3.33 mg/kg bw/da Value 9.25 mg/m ³ 9.25 mg/m ³	Remark	
Product name Ethyl 2-Cyanoacrylate Hydroquinone Applicable limit values when usi If limit values are applicable an Threshold values DNEL/DMEL - Workers ethyl 2-cyanoacrylate Effect level (DNEL/DMEL) DNEL I.4-dihydroxybenzene Effect level (DNEL/DMEL) DNEL I.4-dihydroxybenzene Effect level (DNEL/DMEL) DNEL I.4-dihydroxybenzene	Type Long-term systemic e Acute systemic effect Long-term local effects inl Type Long-term systemic e Acute systemic effect Long-term systemic e Acute systemic effect Long-term local effects inl	OSHA NIOSH OSHA re as intended e listed below ffects inhalation ts inhalation halation ffects inhalat ffects dermal ffects inhalat is inhalation ts inhalation ts inhalation halation	ion ion ion	55 5004 2094 9.25 mg/m ³ 9.25 mg/m ³ 9.25 mg/m ³ 9.25 mg/m ³ Value 2.1 mg/m ³ 3.33 mg/kg bw/da Value 9.25 mg/m ³ 9.25 mg/m ³ 9.25 mg/m ³	y Remark	
Product name Ethyl 2-Cyanoacrylate Hydroquinone Applicable limit values when usi If limit values are applicable an Threshold values DNEL/DMEL - Workers ethyl 2-cyanoacrylate Effect level (DNEL/DMEL) DNEL I.4-dihydroxybenzene Effect level (DNEL/DMEL) DNEL Effect level (DNEL/DMEL) Effect level (DNEL/DMEL) Effect level (DNEL/DMEL) DNEL Effect level (DNEL/DMEL)	Type Long-term systemic e Acute systemic effect Long-term local effects inl Type Long-term systemic e Acute systemic effect Long-term systemic e Acute systemic effect Long-term local effects inl Type Long-term local effects inl	OSHA NIOSH OSHA re as intended e listed below ffects inhalation ts inhalation halation ffects inhalat ffects dermal ffects inhalation ts inhalation ts inhalation ffects inhalat ffects dermal	ion ion ion ion	55 5004 2094 9.25 mg/m ³ 9.25 mg/m ³ 9.25 mg/m ³ 9.25 mg/m ³ Value 2.1 mg/m ³ 3.33 mg/kg bw/da Value 9.25 mg/m ³ 9.25 mg/m ³ 9.25 mg/m ³ 9.25 mg/m ³ 9.25 mg/m ³	Remark y Remark y Remark y Remark y Remark y Remark y Remark	

PNEC

1,4-dihydroxybenzene									
Compartments	Value	Remark							
Fresh water	0.57 μg/l								
Fresh water (intermittent releases)	1.34 μg/l								
Marine water	0.057 μg/l								
STP	0.71 mg/l								
Fresh water sediment	4.9 μg/kg sediment dw								
Marine water sediment	0.49 μg/kg sediment dw								
Soil	0.64 μg/kg soil dw								

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Keep away from naked flames/heat. Measure the concentration in the air regularly. Carry operations in the open/under local exhaust/ventilation or with respiratory protection.

8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Do not eat, drink or smoke during work.

a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

b) Hand protection: Protective gloves against chemicals (EN 274)

	Measured breakthrough time	Thickness	Protection index	Remark			
nitrile rubber	> 480 minutes	0.4 mm	Class 6				

c) Eye protection:

Face shield (EN 166).

d) Skin protection:

Protective clothing (EN 14605 or EN 13034).

8.2.3 Environmental exposure controls:

See sections 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

mormation on basic physical al	a chemical properties
Physical form	Liquid
Odour	Characteristic odour
Odour threshold	No data available in the literature
Colour	Colourless
Particle size	Not applicable (liquid)
Explosion limits	No data available in the literature
Flammability	Not classified as flammable
Log Kow	Not applicable (mixture)
Dynamic viscosity	No data available in the literature
Kinematic viscosity	No data available in the literature
Melting point	No data available in the literature
Boiling point	150 °C
Relative vapour density	No data available in the literature
Vapour pressure	No data available in the literature
Solubility	Water ; insoluble
	Acetone ; soluble
Relative density	1.05
Absolute density	1050 kg/m³
Decomposition temperature	No data available in the literature
Auto-ignition temperature	500 °C
Flash point	87 °C
рН	Not applicable (non-soluble in water)

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Temperature above flashpoint: higher fire/explosion hazard.

10.2. Chemical stability

Unstable on exposure to moisture. Unstable on exposure to air.

10.3. Possibility of hazardous reactions

Polymerizes on exposure to water (moisture) and on exposure to temperature rise: pressure rise and possible bursting of container.

10.4. Conditions to avoid

Precautionary measures

Keep away from naked flames/heat.

10.5. Incompatible materials

(strong) acids, oxidizing agents, water/moisture.

10.6. Hazardous decomposition products

At very high temperature: release of toxic/combustible gases/vapours (hydrogen cyanide). On burning: release of toxic and corrosive gases/vapours (nitrous vapours, carbon monoxide - carbon dioxide).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

11.1.1 Test results

Acute toxicity

<u>SUPER</u>

No (test)data on the mixture available

Judgement is based on the relevant ingredients

ethyl 2-cyanoacrylate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark
						determination	
Oral	LD50	Equivalent to OECD 423	> 5000 mg/kg bw		Rat (male)	Experimental value	
Skin	LD50	Equivalent to OECD 402	> 2000 mg/kg bw	24 h	Rabbit (male)	Experimental value	
Inhalation						Data waiving	

1.4-dihvdroxybenzene

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark
						determination	
Oral	LD50	OECD 401	> 375 mg/kg bw			Experimental value	
					female)		
Dermal	LD50	OECD 402	> 2000 mg/kg bw	24 h	Rabbit (male / female)	Experimental value	
Inhalation (aerosol)	LC50		≥ 7.8 mg/l air	1 h	Rat (female)	Read-across	

Conclusion

Not classified for acute toxicity

Corrosion/irritation

<u>SUPER</u>

No (test)data on the mixture available

Classification is based on the relevant ingredients

ethyl 2-cyanoacrylate

Route of exposure	Result	Method	Exposure time	Time point		Value determination	Remark
Eye	Irritating	Equivalent to OECD 405	72 h	24; 48; 72 hours	Rabbit	Experimental value	
Skin	Slightly irritating	Equivalent to OECD 404	24 h	24; 72 hours	Rabbit	Experimental value	
Skin	Irritating; category 2					Annex VI	
Inhalation	Irritating; STOT SE cat.3					Annex VI	

Reason for revision: 3; 9; 12

	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Serious eye damage; category 1					Annex VI	
Skin	Not irritating		24 h	24 hours	Rat	Weight of evidence	
tory or skin sensitis o (test)data on the r dgement is based o hyl 2-cyanoacrylate Route of exposure	nixture available n the relevant ing	redients Method	Exposure time	Observation time	Species	Value determination	Remark
				point		E 1 1 1	
Skin	Not sensitizing	Guinea pig maximisation test				Experimental value	
Skin 4-dihydroxybenzene	Ū	Guinea pig maximisation test			/ female)	Experimental value	
-	2		Exposure time	Observation time point		Experimental value	Remark
4-dihydroxybenzene	2	maximisation test	Exposure time 3 day(s)		/ female)		Remark
4-dihydroxybenzene Route of exposure	2 Result	Method Equivalent to OECD			/ female) Species	Value determination	Remark

<u>SUPER</u>

No (test)data on the mixture available

Judgement is based on the relevant ingredients

ethyl 2-cyanoacrylate

	Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value
									determination
	Oral								Data waiving
	Dermal								Data waiving
	Inhalation								Data waiving
<u>1,4</u>	dihydroxybenzene			-					

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time		Value determination
Oral (stomach tube)	NOAEL	Equivalent to OECD 453	25 mg/kg bw/day		No effect	65 weeks (5 days / week) - 104 weeks (5 days / week)	Rat (male)	Experimental value
Dermal		Equivalent to OECD 411	73.9 mg/l - 109.6 mg/l		No effect	13 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value
Inhalation								Data waiving

Conclusion

Not classified for subchronic toxicity

Mutagenicity (in vitro)

<u>SUPER</u>

No (test)data on the mixture available

Judgement is based on the relevant ingredients

ethyl 2-cyanoacrylate

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	OECD 473	Human lymphocytes	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	OECD 476	Mouse (lymphoma L5178Y cells)	No effect	Experimental value	

Reason for revision: 3; 9; 12

Publication date: 2000-09-22 Date of revision: 2022-07-28

Revision number: 1100

BIG number: 32181

-dihydroxybenzene						
Result	Method	Test substrate	Effect	Value determination	Remark	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value		
Positive with metabolic activation, positive without metabolic activation	Equivalent to OECD 476	Mouse (lymphoma L5178Y cells)		Experimental value		

Mutagenicity (in vivo)

<u>SUPER</u>

No (test)data on the mixture available

Judgement is based on the relevant ingredients

1,4-dihydroxybenzene

Result	Method	Exposure time	Test substrate	Organ	Value determination
Positive (Oral (stomach tube))	Equivalent to OECD 483		Mouse (male)		Experimental value
Negative (Oral (stomach tube))	Equivalent to OECD 478	10 weeks (5 days / week)	Rat (male)		Experimental value

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

<u>SUPER</u>

No (test)data on the mixture available

Judgement is based on the relevant ingredients

1,4-dihydroxybenzene

Route of	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
exposure								
Oral	Dose level	Equivalent to OECD 453	50 mg/kg bw/day	65 weeks (5 days / week) - 104 weeks (5 days / week)	Rat (male)	Tumor formation	Kidney	Experimental value
Oral	Dose level	Equivalent to OECD 453	bw/day	65 weeks (5 days / week) - 104 weeks (5 days / week)	Rat (female)	Change in the haemogramme/ blood composition	Blood	Experimental value

Conclusion

Not classified for carcinogenicity

Reproductive toxicity

<u>SUPER</u>

No (test)data on the mixture available

Judgement is based on the relevant ingredients ethyl 2-cyanoacrylate

	Parameter	Method	Value	Exposure time	Species	Effect	- 0.	Value determination
Developmental toxicity								Data waiving
Effects on fertility								Data waiving
4-dihydroxybenzene				•				

	Parameter	Method	Value	Exposure time	Species	Effect	- 0-	Value determination
Developmental toxicity (Oral (stomach tube))	NOEL		100 mg/kg bw/day	10 day(s)	Rat	No effect		Experimental value
Maternal toxicity (Oral (stomach tube))	NOEL		100 mg/kg bw/day	10 day(s)	Rat	No effect		Experimental value
Effects on fertility (Oral (stomach tube))	NOAEL (F1/F2)		150 mg/kg bw/day	40 weeks (daily)	Rat (male / female)	No effect		Experimental value

Conclusion

Not classified for reprotoxic or developmental toxicity

Toxicity other effects

<u>SUPER</u>

No (test)data on the mixture available

Chronic effects from short and long-term exposure

<u>SUPER</u>

Reason for revision: 3; 9; 12

No effects known.

11.2. Information on other hazards

No evidence of endocrine disrupting properties

SECTION 12: Ecological information

12.1. Toxicity

<u>SUPER</u>

No (test)data on the mixture available

Judgement of the mixture is based on the relevant ingredients

1,4-dihydroxybenzene

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Equivalent to OECD 203	0.638 mg/l	96 h	Oncorhynchus mykiss	Flow- through system	Fresh water	Experimental value; Lethal
Acute toxicity crustacea	EC50	Equivalent to OECD 202	0.061 mg/l	48 h	Daphnia magna	Semi-static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	ErC50	Equivalent to OECD 201	0.053 mg/l	72 h	Pseudokirchneri ella subcapitata	Static system	Fresh water	Experimental value; GLP
Long-term toxicity fish	NOEC	OECD 210	≥ 66 µg/l	32 day(s)	Pimephales promelas	Flow- through system	Fresh water	Experimental value; Reproduction
Long-term toxicity aquatic crustacea	NOEC	OECD 211	0.006 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; Reproduction
Toxicity aquatic micro- organisms	IC50		71 mg/l	2 h	Activated sludge	Static system	Fresh water	Experimental value; Respiration

Conclusion

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

12.2. Persistence and degradability

<u>ethyl 2-cyanoacrylate</u>
Biodegradation water

	Method	Value	Duration	Value determination
	EU Method C.4-A	98 %	28 day(s)	Read-across
1,4	-dihydroxybenzene			

Biodegradation water

ы	odegradation water							
	Method	Value	Duration	Value determination				
	OECD 301C	70 %; Oxygen consumption	14 day(s)	Experimental value				
Bi	Biodegradation soil							
	Method	Value	Duration	Value determination				
		100 %	1 day(s)	Experimental value				

Conclusion

Water

Does not contain any not readily biodegradable component(s)

12.3. Bioaccumulative potential

<u>SUPER</u>

Log Kow

[Method	Remark	Value	Temperature	Value determination		
[Not applicable (mixture)					

ethyl 2-cyanoacrylate

BCF	fishes

	Parameter	Method		Value	Duration	Species		Value determination
				No data available				
				(test not performed)				
Lo	og Kow							
	Method		Remark		Value		Temperature	Value determination
	EU Method A.8				0.776		22 °C	Experimental value

1,4-dihydroxybenzene

Parameter Method		Value	Duration	Species		Value determination	
BCF	BCFBAF v3	.00	3.162 l/kg				Estimated value
og Kow							
		Remark		Value		Temperature	Value determination
Method							

Conclusion

(log) Koc

Does not contain bioaccumulative component(s)

12.4. Mobility in soil

ethyl 2-cyanoacrylate

			-	
	Parameter	Method	Value	Value determination
	log Koc	SRC PCKOCWIN v2.0	0.834	Calculated value
1.	1-dibydroxybenzene			

	Parameter							Value		Value determination
	log Koc							0.97 - 1.5	585	Estimated value
P	Percent distribution									
	Method	Fraction air	Fraction biota	Fraction		Fraction soil	Fraction	water	Value determ	ination
				sediment	t					
	Mackay level I						99.9 %		Experimental	value

Conclusion

Contains component(s) with potential for mobility in the soil

12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties

12.7. Other adverse effects

<u>SUPER</u>

Greenhouse gases None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014) Ozone-depleting potential (ODP) Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009) Groundwater Groundwater pollutant

<u>ethyl 2-cyanoacrylate</u> Groundwater Groundwater pollutant

<u>1.4-dihydroxybenzene</u> Groundwater Groundwater pollutant Water ecotoxicity pH pH shift

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

European Union

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997. Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

08 04 09* (wastes from MFSU of adhesives and sealants (including waterproofing products): waste adhesives and sealants containing organic solvents or other hazardous substances). Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

13.1.3 Packaging/Container

European Union

Reason for revision: 3; 9; 12

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14: Transport information

Road (ADR), Rail (RID), Inland waterways (ADN), Sea (IMDG/IMSBC), Air (ICAO-TI/IATA-DGR)

14. <u>1. UN number</u>			
Transport	Not subject		
14.2. UN proper shipping name			
14.3. Transport hazard class(es)			
Hazard identification number			
Class			
Classification code			
14.4. Packing group			
Packing group			
Labels			
4.5. Environmental hazards			
Environmentally hazardous substance mark	no		
4.6. Special precautions for user			
Special provisions			
Limited quantities			
14.7. Maritime transport in bulk according to IMO instruments			
Annex II of MARPOL 73/78	Not applicable, based on available data		

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
2 %	
20 g/l	

Directive 2012/18/EU (Seveso III)

Not subject to registration according to Directive 2012/18/EU (Seveso III)

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
ethyl 2-cyanoacrylate	Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	 Shall not be used in: ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, tricks and jokes, games for one or more participants, or any article intended to be used as such, even wit ornamental aspects, Articles not complying with paragraph 1 shall not be placed on the market. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: can be used as fuel in decorative oil lamps for supply to the general public, and,
ethyl 2-cyanoacrylate 1,4-dihydroxybenzene	Substances falling within one or more of the following points: (a) substances classified as any of the following in Part 3 of Annex VI to Regulation (EC) No 1272/2008: — carcinogen category 1A, 1B or 2, or germ cell mutagen category 1A, 1B or 2, but excluding any such substances classified due to effects only following	Mixtures for tattooing purposes are subject to the restrictions of Regulation (EU) 2020/208
on for revision: 3; 9; 12		Publication date: 2000-09-22
		Date of revision: 2022-07-28

	SUPER
	exposure by inhalation
	- reproductive toxicant category 1A, 1B or 2
	but excluding any such substances classified
	due to effects only following exposure by inhalation
	— skin sensitiser category 1, 1A or 1B
	- skin corrosive category 1, 1A, 1B or 1C or
	skin irritant category 2
	- serious eye damage category 1 or eye
	irritant category 2
	(b) substances listed in Annex II to Regulation (EC) No 1223/2009 of the European
	Parliament and of the Council
	(c) substances listed in Annex IV to Regulation
	(EC) No 1223/2009 for which a condition is specified in at least one of the columns g, h
	and i of the table in that Annex (d) substances
	listed in Appendix 13 to this Annex.
	The ancillary requirements in paragraphs 7
	and 8 of column 2 of this entry apply to all mixtures for use for tattooing purposes,
	whether or not they contain a substance
	falling within points (a) to (d) of this column of
	this entry.
National legislation Belgium	
SUPER	
No data available	
National legislation The Netherlands SUPER	<u>i</u>
Waterbezwaarlijkheid	B (4); Algemene Beoordelingsmethodiek (ABM)
National legislation France	
SUPER	
No data available	
1,4-dihydroxybenzene	
Catégorie cancérogène	Hydroquinone; C2
Catégorie mutagène	Hydroquinone; M2
National legislation Germany	
SUPER	1
WGK	1; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017
ethyl 2-cyanoacrylate	1
TA-Luft	5.2.5
1,4-dihydroxybenzene TA-Luft	5.2.5/I
National legislation Austria	_J.z. J1
SUPER	
No data available	
<u>1,4-dihydroxybenzene</u>	
Krebserzeugend	1,4-Dihydroxybenzol; III B
Gefahr der Sensibilisierung der	1,4-Dihydroxybenzol; S
Haut Gefahr der Sensibilisierung der	1,4-Dihydroxybenzol; S
Atemwege	
National legislation United Kingdom	
SUPER	
No data available	
Other relevant data SUPER	
No data available	
ethyl 2-cyanoacrylate	
TLV - Skin Sensitisation	Cyanoacrylates, Ethyl and Methyl; SEN; Sensitization
TLV - Respiratory Sensitisation	Cyanoacrylates, Ethyl and Methyl; SEN; Sensitization
<u>1,4-dihydroxybenzene</u>	
TLV - Skin Sensitisation	Hydroquinone; SEN; Sensitization
TLV - Carcinogen	Hydroquinone; A3
IARC - classification	3; Hydroquinone
5.2. Chemical safety assessme	
=	as been conducted for the mixture.
no chemical safety assessmellt li	
on for revision: 3; 9; 12	Publication date: 2000-09-22

Date of revision: 2022-07-28

BIG number: 32181

SECTION 16: Other information

Full text of any H- and EUH-statements referred to under section 3:

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

- H341 Suspected of causing genetic defects.H351 Suspected of causing cancer.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

EUH202 Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

(*)	INTERNAL CLASSIFICATION BY BIG
ADI	Acceptable daily intake
AOEL	Acceptable operator exposure level
ATE	Acute Toxicity Estimate
CLP (EU-GHS)	Classification, labelling and packaging (Globally Harmonised System in Europe)
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
EC50	Effect Concentration 50 %
ErC50	EC50 in terms of reduction of growth rate
LC50	Lethal Concentration 50 %
LD50	Lethal Dose 50 %
NOAEC/NOAEL	No Observed Adverse Effect Concentration/No Observed Adverse Effect Level
NOEC/NOEL	No Observed Effect Concentration/No Observed Effect Level
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent, Bioaccumulative & Toxic
PNEC	Predicted No Effect Concentration
STP	Sludge Treatment Process
vPvB	very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 3; 9; 12